

**Claims:**

1           1.    In a wireless communication system including a  
2 plurality of wireless communication system network components  
3 intercoupled by a wired network, a method for distributing a  
4 file from a network component acting as a sender to a  
5 plurality of network components acting as receivers, the  
6 method comprising:

7           the sender establishing a multicast session with the  
8 plurality of receivers;

9           the sender subdividing the file into a plurality of data  
10 packets;

11          the sender multicasting the plurality of data packets to  
12 the plurality of receivers;

13          at least some of the plurality of receivers failing to  
14 correctly receive all of the plurality of data packets;

15          the at least some of the plurality of receivers failing  
16 to correctly receive all of the plurality of data packets  
17 error reporting to the sender of the plurality of data  
18 packets; and

19          the sender transmitting a plurality of previously  
20 incorrectly received data packets of the plurality of data  
21 packets to the at least some of the plurality of receivers.

2. The method of claim 1, wherein the sender is a base station manager.

3. The method of claim 1, wherein the receivers are base station controllers.

4. The method of claim 1, wherein the receivers are base stations.

5. The method of claim 4, wherein:  
the base stations operate according to a code division multiple access wireless operating standard; and  
the base stations load the file onto a plurality of processing cards contained within the base stations.

6. The method of claim 1, wherein:  
the plurality of receivers comprise a group of network components requiring a software update; and  
the file comprises the software update.

7. The method of claim 1, wherein error reporting to the sender comprises:  
the sender transmitting an error status request to the plurality of receivers; and  
at least one of the plurality of receivers responding to the sender with an error message.

1           8.    The method of claim 1, wherein error reporting to  
2 the sender comprises:

3           the sender sends an error status request to a first  
4 plurality of receivers during a first time period;

5           the sender sends an error status request to a second  
6 plurality of receivers during a second time period; and

7           wherein the first time period is different from the  
8 second time period.

1           9.    The method of claim 1, wherein transmitting a  
2 plurality of previously incorrectly unreceived data packets  
3 of the plurality of data packets to the at least some of the  
4 plurality of receivers comprises:

5           the sender determining a subset of receivers that failed  
6 to correctly receive all of the plurality of data packets;

7           the sender of the file determining a corresponding set  
8 of data packets that were not previously incorrectly received  
9 by the subset of receivers; and

10          the sender of the file multicasting the corresponding  
11 set of data packets to the subset of receivers.

1           10.   A system for distributing a file within a wireless  
2 communication network, the system comprising:

3           a server network component of the wireless communication  
4 network, the server network component comprising:

5           a processor;

6           a memory coupled to the processor; and

7           a network interface coupled to the processor;

8           a plurality of receiver network components of the

9 wireless communication network, each of the receiver network

10 components comprising:

11           a processor;

12           a memory coupled to the processor; and

13           a network interface coupled to the processor; and

14           a plurality of software instructions executable by the

15 sender network component and the plurality of receiver

16 network components, the plurality of software instructions

17 comprising:

18           a first set of sender software instructions that,

19 when executed by the processor of the sender, causes the

20 sender to establish a multicast session with the plurality of

21 receiver network components;

22           a first set of receiver software instructions that,

23 when executed by a receiver, causes the receiver to interact

24 with the sender to join the multicast session;

25           a second set of sender software instructions that,

26 when executed by the processor of the sender, causes the

27 sender to subdivide the file into a plurality of data

28 packets;

29           a third set of sender software instructions that,

30 when executed by the processor of the sender causes the

31 sender to multicast the plurality of data packets to the

32 plurality of receivers;

33           a second set of receiver instructions that, when

34 executed by the processor of a receiver that fails to  
35 correctly receive all of the plurality of data packets,  
36 causes the receiver to error report to the sender; and

37 a fourth set of sender software instructions that,  
38 when executed by the processor of the sender, causes the  
39 sender to transmit a plurality of incorrectly received data  
40 packets of the plurality of data packets to the receiver that  
41 fails to correctly receive all of the plurality of data  
42 packets.

1 11. The system of claim 10, wherein the sender is a  
2 base station manager.

1 12. The system of claim 10, wherein the receivers are  
2 base station controllers.

1 13. The system of claim 10, wherein the receivers are  
2 base stations.

1 14. The system of claim 13, wherein:  
2 the base stations operate according to a code division  
3 multiple access wireless operating standard; and  
4 the base stations load the file onto a plurality of  
5 processing cards contained within the base stations.

1 15. The system of claim 10, wherein:  
2 the plurality of receivers comprise a group of network

components requiring a software update; and  
the file comprises the software update.

16. The system of claim 10, further comprising:  
a fifth set of sender software instructions that, when  
executed by the processor of the sender, causes the sender to  
transmit an error status request to the plurality of  
receivers; and  
a sixth set of sender software instructions that, when  
executed by the processor of the sender, causes the sender to  
receive an error status response from at least some of the  
plurality of receivers.

17. The system of claim 11, wherein the fifth set of  
sender software instructions further causes:  
the sender to transmit an error status request to a  
first plurality of receivers during a first time period;  
the sender to transmit an error status request to a  
second plurality of receivers during a second time period;  
and  
wherein the first time period is different from the  
second time period.

18. The system of claim 10, further comprising a fifth  
set of sender instructions that, when executed by the  
processor of the sender, causes the sender to:  
determine a subset of receivers that failed to correctly

```

5   receive all of the plurality of data packets;
6       determine a corresponding set of data packets that were
7   not correctly received by the subset of receivers; and
8       multicast the corresponding set of data packets to the
9   subset of receivers.

```

1       19. A system for distributing a file within a wireless  
2       communication network, the system comprising:

3       a server protocol suite operating on a sender component  
4   of the wireless communication network;

5       a plurality of receiver protocol suites operating on a  
6 plurality of receiver network components of the wireless  
7 communication network, wherein each of the plurality of  
8 receiver network components is communicatively coupled to the  
9 sender component;

```

10         wherein the server protocol suite causes the sender to
11     establish a multicast session with the plurality of receiver
12     network components;

```

```

13         wherein the receiver protocol suite causes the plurality
14 of receivers to interact with the sender to join the
15 multicast session;

```

16       wherein the server protocol suite causes the sender to  
17       subdivide the file into a plurality of data packets;

```

18         wherein the server protocol suite causes the sender to
19         multicast the plurality of data packets to the plurality of
20         receivers;

```

21 wherein the receiver protocol suite causes the plurality

22 of receivers to error report to the sender; and  
23 the server protocol suite causes the sender to transmit  
24 a plurality of incorrectly received data packets of the  
25 plurality of data packets to a receiver that fails to  
26 correctly receive all of the plurality of data packets.

1 20. The system of claim 19, wherein the sender is a  
2 base station manager.

1 21. The system of claim 19, wherein the receivers are  
2 base station controllers.

1 22. The system of claim 19, wherein the receivers are  
2 base stations.

1 23. The system of claim 22, wherein:  
2 the base stations operate according to a code division  
3 multiple access wireless operating standard; and  
4 the base stations load the file onto a plurality of  
5 processing cards contained within the base stations.

1 24. The system of claim 19, wherein:  
2 the plurality of receivers comprise a group of network  
3 components requiring a software update; and  
4 the file comprises the software update.

1 25. The system of claim 19:



2 wherein the server protocol suite causes the sender to  
3 transmit an error status request to the plurality of  
4 receivers; and

5 wherein the receive protocol suite causes each of the  
6 plurality of receivers to respond to the sender with an error  
7 status response.

1 26. The system of claim 19, wherein the server protocol  
2 suite causes the sender to:

3 transmit an error status request to a first plurality of  
4 receivers during a first time period;

5 transmit an error status request to a second plurality  
6 of receivers during a second time period; and

7 wherein the first time period is different from the  
8 second time period.

1 27. The system of claim 19, wherein the server protocol  
2 suite causes the sender to:

3 determine a subset of receivers that failed to correctly  
4 receive all of the plurality of data packets;

5 determine a corresponding set of data packets were not  
6 correctly received by the subset of receivers; and

7 multicast the corresponding set of data packets to the  
8 receivers comprising the subset of receivers that failed to  
9 correctly receive all of the plurality of data packets.